



Fuse-link, low voltage, 200 A, AC 415 V, 80 kA, BS88, 31 x 110 mm, gL/gG, BS



Part no. 200AMP 415V AC BS88 FUSE
Catalog No. DE0200

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	200
Rated voltage			AC 415 V
Construction size			BS88
Size			31 x 110 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			general industrial applications
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88 IEC 60269

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			AC
Rated voltage AC		V	415
Rated voltage DC		V	
Rated current		A	200
Utilization category			gL/gG (cable protection/equipment protection)
Breaking capacity		kA	80
Colour code			None
Type of fuse status indicator			None
Power loss at rated current		W	14
Mounting holes			M8
Centre-to-centre distance of connections		mm	93.7