



Fuse-link, high speed, 125 A, AC 690 V, 200 kA, DIN 00, 30 x 60 x 79 mm, gR, DIN, IEC, type T indicator, live gripping lugs

Part no. **FUSE 125A 690V DIN 00 GR**
Catalog No. **170M2701**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	125
Rated voltage			AC 690 V
Construction size			DIN 00
Size			30 x 60 x 79 mm
Utilization category			gR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ec1@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	125
Utilization category			gR (general purpose semiconductor protection)
Breaking capacity		kA	
Colour code			
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	23
Mounting holes			
Centre-to-centre distance of connections		mm	

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720019_170M.pdf
-------------------------	---