

**H95,0/25****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

For conductors from 10.0 to 185.0 mm<sup>2</sup> (AWG 7 - 350 MCM)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in poly-bag

**General ordering data**

|            |                                              |
|------------|----------------------------------------------|
| Version    | Wire-end ferrule, Standard, 25 mm, 25 mm, No |
| Order No.  | <a href="#">9004250000</a>                   |
| Type       | H95,0/25                                     |
| GTIN (EAN) | 4008190075576                                |
| Qty.       | 50 pc(s).                                    |
| Packaging  | loose                                        |

**H95,0/25****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |        |
|------------|--------|
| Net weight | 4.02 g |
|------------|--------|

**Technical data**

|                        |                                         |         |          |
|------------------------|-----------------------------------------|---------|----------|
| Description of article | Wire end ferrule without plastic collar | Version | Standard |
|------------------------|-----------------------------------------|---------|----------|

**Wire-end ferrules**

|                                         |         |                             |                    |
|-----------------------------------------|---------|-----------------------------|--------------------|
| Collar diameter (D2)                    | 17 mm   | Conductor cross-section     | 95 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 14.5 mm | Contact surface length (L2) | 25 mm              |
| L1 in mm                                | 25 mm   | Stripping length            | 25 mm              |
| Wire connection cross section AWG, max. | AWG 3/0 |                             |                    |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |
| ECLASS 14.0 | 27-40-02-01 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

**H95,0/25**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

Drawings

