

PRODUCT-DETAILS

CA5-04N

CA5-04N Auxiliary Contact Block



General Information

Extended Product Type	CA5-04N
Product ID	1SBN010040R1204
EAN	3471522121196
Catalog Description	CA5-04N Auxiliary Contact Block
Long Description	CA5-04N Auxiliary Contact Block

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85389099
Product Main Type	Accessories for Block Contactors

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and Manuals	1SBC101012M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	43 mm
Product Net Depth / Length	39 mm
Product Net Height	47 mm
Product Net Weight	0.06 kg

Technical

Maximum Electrical Switching Frequency	1200 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Mechanical Durability	10 million
Minimum Switching Capacity	N 17 / 5 VLT4K
Mounting Position	Front face
Mounting Type	Front mounting
Number of Auxiliary Contacts NC	4
Number of Auxiliary Contacts NO	0
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Remarks	100
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Suitable For	N22E N31E N40E NL22E NL31E NL40E TNL22E TNL31E TNL40E
Technical Information	CA5-04N (4XNC)
Terminal Type	Screw Terminals

Technical UL/CSA

Pilot Duty UL/CSA

A600

Q300

Environmental

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Information	2CMT2021-006277
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE_62119A1
CCC Certificate	CCC_2015010304800518
CQC Certificate	CQC2015010304800518 CQC2004010305133985
Declaration of Conformity - CCC	2020980304001627 2020980305001185
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
DNV GL Certificate	DNV_GL_TAE00001UT
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07174
RINA Certificate	RINA_ELE172319XG001

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	43 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522121196
Package Level 2 Units	box 200 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	36000 piece

Classifications

eClass	V11.0 : 27371302
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
Object Classification	K

Code	
UNSPSC	39121522

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

