

# EAO – Your Expert Partner for Human Machine Interfaces

## 704.064.2 - Stop switch actuator

### 704.064.2 - Stop switch actuator

*Attention: The preview is based on a sample product. This can differ from your current configuration.*

#### Mounting

|                  |           |
|------------------|-----------|
| Mounting cut-out | Ø 22,3 mm |
| Design           | raised    |

#### Front

|                 |         |
|-----------------|---------|
| Front shape     | round   |
| Front dimension | Ø 37 mm |

#### Other Attributes

|         |          |
|---------|----------|
| Marking | Arrows   |
| Weight  | 0,300 kg |

#### Operating-/Indication part

|                   |                  |
|-------------------|------------------|
| Lens material     | Plastic          |
| Lens optics       | opaque           |
| Lens profile      | Mushroom         |
| Lens colour       | red              |
| Lens illumination | non-illuminative |

#### IP-Rating

|                  |      |
|------------------|------|
| Front protection | IP65 |
|------------------|------|

#### Actuator

|                  |            |
|------------------|------------|
| Switching action | Maintained |
| Housing colour   | yellow     |
| Housing material | Plastic    |

#### Switching element

|                                   |   |
|-----------------------------------|---|
| max. number of switching elements | 3 |
|-----------------------------------|---|


#### Function

|             |
|-------------|
| Stop switch |
|-------------|

# EAO – Your Expert Partner for Human Machine Interfaces


## 704.064.2 - Stop switch actuator

## Dimensions



X = Screw terminal

## Mounting cut-outs



## Wiring diagram



### Additional information

Shaft yellow

Twist to unlock anti-clockwise

Max. 3 slow-make elements can be clipped on

### Legend

Switching action: C = Maintained