



Fuse-link, 200 A, AC 1000 V, 125 kA, size 00, 30 x 47 x 98 mm, aR, DIN, IEC, single indicator



Part no. FUSE 200A 1000V 00/80 AR
Catalog No. 170M4813

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	200
Rated voltage			AC 1000 V
Construction size			size 00
Size			30 x 47 x 98 mm
Utilization category			aR
Status indicator			single indicator
Breaking Capacity		kA	125
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4
Optional accessories			fuse-holder 170H1007

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			Other
Rated current		A	200
Rated voltage		V	1000
Voltage type			AC
Rated switching capacity		kA	125
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No