

DATASHEET - FUSE 1250A 1000V 3FKE/115AR CU



Fuse-link, high speed, 1250 A, AC 1000 V, 100 kA, size 3, 76 x 92 x 159 mm, aR, IEC, UL, type K indicator, US style



Part no. FUSE 1250A 1000V 3FKE/115AR CU
Catalog No. 170M6750

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1250
Rated voltage			AC 1000 V
Construction size			size 3
Size			76 x 92 x 159 mm
Utilization category			aR
Status indicator			type K indicator
Description			US style
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			3
Type of current			AC
Rated voltage AC		V	1000
Rated voltage DC		V	
Rated current		A	1250
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	100
Colour code			None
Type of fuse status indicator			Other
Power loss at rated current		W	145
Mounting holes			Other
Centre-to-centre distance of connections		mm	114